



Model # 1845

3/4\"/>

SALES AND MARKETING
 2417 SEAMAN AVENUE
 SOUTH EL MONTE, CA 91733
 Phone: (800) 221-9705
 USA Toll Free
 Fax: (877) 318-2194
 Phone: (626) 228-3170
 Fax: (626) 228-3124

372 OLD US HIGHWAY
 52 SOUTH
 MT. AIRY, NC 27030
 (800) 221-9705
 Phone: (336) 786-6432
 Fax: (336) 786-4992

DURABLE

Twin hammer mechanism

RELIABILITY

Aluminum housing and long lasting motor with iron plate

MAXIMUM CONTROL

3 power settings in forward and reverse

FRICTION RING

Common retainer for 3/4\"/>

GREAT CONTROL

Full teasing trigger

INSULATION & COMFORT

Rubber grip for a durable and comfortable use

QUITE & HANDLE EXHAUSE

Decreases fatigue of the operator

Model	Square Driver	Free Speed	Bolt Capacity	Max. Torque	Air Hose I.D. Size
1845	3/4"	7,200rpm	1-1/4" (32mm)	1100 ft-lb (1490Nm)	3/8" (10mm)
Air Inlet Thread NPT	Avg. Air Consumption	Noise Level	Vibration	Overall Length	Net Weight
1/4"	0.23 m³/min	87 dBA	4.5 m/s²	6.96" (177mm)	5.8lbs (2.64kgs)

EXCELLENT POWER-TO-WEIGHT RATIO

- Anvil and hammer are constructed of Ni-Cr-Mo alloy steel with heat treatment for long trouble-free service
- Rigid hammer housing made of hot forged machined steel
- One-piece hammer housing with pilot lip provides maximum alignment from motor to anvil
- Variable power control
- Six-position power management/regulator (3 forward & 3 reverse)
- Refined twin hammer impact mechanism and high speed motor increases energy of each blow while doubling the life



Astro

E-mail : astrotools@astrotools.com
 WEBSITE : www.astrotools.com



AIR TOOLS

SHOP EQUIPMENT PAINT & BODY UNDERCAR KIT HYDRAULICS

