



Model # EVOT13
(1.3mm nozzle)

EVOT14
(1.4mm nozzle)

**EUROPRO FORGED
EVO-T SPRAY GUN
W/ PLASTIC CUP**

SALES AND MARKETING

2417 SEAMAN AVENUE
SOUTH EL MONTE, CA 91733
Phone: (800) 221-9705
USA Toll Free
Fax: (877) 318-2194
Phone: (626) 228-3170
Fax: (626) 228-3124

372 OLD US HIGHWAY
52 SOUTH
MT. AIRY, NC 27030
(800) 221-9705
Phone: (336) 786-6432
Fax: (336) 786-4992



Astro

E-mail : astrotools@astrotools.com
WEBSITE : www.astrotools.com



PAINT & BODY



**Low Air Consumption –
Highest Transfer Efficiency**



SMOOTH OPERATION

- Soft trigger pull to reduce fatigue
- Precise lubricated adjustment knobs for better control
- Innovative CNC machining to avoid the need for gaskets behind the fluid tip



HIGH EFFICIENCY

- Innovative, advanced EVO-T technology US Patent# US 7,237,727 B2
- "Air Curtain" design to minimize overspray and pollution
- Superior transfer efficiency to reduce paint consumption, as tested in the lab of Fraunhofer IPA, Germany
- Finest atomization & classic quality

DURABLE & LIGHTWEIGHT

- Forged body provides longer tool life
- Anodized body for corrosion protection
- Internal coated passages
- Stainless steel needle and fluid tip
- Slick finish for faster & easier cleaning
- Lightweight: 285 grams (0.6 lbs)

QUICK THREAD TECHNOLOGY

- 1.5 Turn to lock/unlock the air cap
- 3 Turns to lock/unlock the fluid nozzle
- 4 Turns to lock/unlock the fluid cup
- Wide threads for easy cleaning
- M16*P1.5 female thread fluid joint
- Compatible with most traditional and disposable cup systems

Model	Nozzle Size	Cup Capacity	Operation Pressure	Air Cap Output
EVOT13 EVOT14	1.3mm, 1.4mm	600ml	15-19psi	10psi
Air Hose I.D. Size	Air Inlet Thread NPT	Avg. Air Consumption	Weight	
6-8mm	1/4"	11.5-13.5cfm	0.6lbs. (285g)	
Required Compressor	Max. Pattern at 4" to 7" Distance	Gun Dimensions W x H		
2.2-3.7hp	9" to 10-1/4" (230-260mm)	7" x 5-3/4" (175mm x 145mm)		

**COMPATIBLE WITH SOLVENT &
WATERBORNE PAINTS**

SHOP EQUIPMENT UNDERCAR KIT HYDRAULICS AIR TOOLS

